



HSM 8 TE



HSM 8 TE horizontal baling press

In terms of performance, efficiency and flexibility our mobile HSM 8 TE small baler is hard to beat. This compact baling press is extremely easy to operate: insert the strapping tape, switch it on and watch it go! The strapping and ejection of the bales is executed with ease. The complete bale ejection means that the compact bales are ejected by the machine directly onto a pallet and can be easily transported to a storage location.

Technical data

Order number:	6208194	Loading aperture width x Loading aperture length:	645 x 730 mm
EAN	4026631064293	Bale width x Bale height x Bale length:	650 x 505 x 500 mm
Pressing power:	80 kN	Bale weight (up to):	70 kg
Specific pressing power:	24,37 N/cm ²	Method of loading:	manual
Driving power:	4 kW	Length x Width x Height:	2505 x 813 x 868 mm
Voltage / Frequency:	400 V / 50 Hz	Weight:	554 kg
Cycle time when idling:	26 s	Type of consumables:	Strapping tape
Volume throughput in idle operation (theor.):	4,38 m ³ /h	Press material:	Plastic film, Mixed paper, Cardboard, Getränke und Aluminiumdosen
Loading height:	660 mm		

Product information



Mobile on castors



Suitable for cardboard as well as film



Compaction against counterplate by horizontal moving press ram



Compact design

Low overall height, large loading aperture, also suitable for bulky material.



Graphic-capable display

Intuitive, multilingual operational guidance via graphic description.



Feeding manual

The extremely large loading aperture makes the unit simple and convenient to load.



Press ram

Compaction against counterplate by horizontal moving press ram.



Automatic bale ready signal

Automatic information as soon as enough material for a bale has been compressed and the bale can be tied.



Strapping

Manual bale strapping with continuous polyester tape.

