



HSM AK 807

Channel baling press HSM AK 807

For industrial applications with small material loads - Troughput up to approx. $36 \text{ m}^3\text{/h}$

Technical data

Pressing power: 82 kN R Loading aperture length: Specific pressing power: 32,8 N/cm² Bale width x Bale height x Bale height x Bale length: Triving power: 4 kW R Bale length: 3940 x 1140 x 1310 mm
Driving power: 4 kW x Bale length: 300 x 300 x 400-300 mm x Bale length: 300 x 1140 x 1210 mm
Length v Width v Height: 2040 v 1140 v 1210 mm
Length x Width x Height: 3940 x 1140 x 1310 mm
Voltage / Frequency: 400 V / 50 Hz
Cycle time when idling: 17,6 s Weight: 1 t
Volume throughput in 36 m³/h Type of consumables: Strapping tape
idle operation (theor.): Press material: Mixed paper, Cardboard,
Volume throughput at 1.8 t/h Plastic film 50kg/m³ (theor.):

Product information



Mainly compresses cardboard and light paper



Manual bale strapping with continuous polyester tape




Integration into automated industrial production processes





System solution

Integration into automated industrial production processes.



Continuous loading

Suitable for continuous loading with conveyor belt, air feeding or similar.



Compact bales

The bales can be stacked and are easy to transport.



Automatic operation

Control of the pressing process via light barrier.



Operating side

Can be fully integrated into existing workflows and processes. Operating side can be selected.



Sturdy design

Very low space requirement thanks to compact and sturdy design.

