



HSM V-Press 1160



HSM V-Press 1160 eco vertical baling press

With a maximum bale weight of 550 kg, strong pressing power and an absolutely high efficiency level, the HSM V-Press 1160 is the top-model of the HSM V-Press series.

Technical data

Order number:	6140184	Loading aperture width x height:	1195 x 650 mm
EAN	4026631056403	Bale length x Bale width x Bale height:	1200 x 1100 x 1200 mm
Pressing power:	594 kN	Bale weight (up to):	550 kg
Specific pressing power:	45 N/cm ²	Width x Depth x Height:	1780 x 1388 x 2985 mm
Driving power:	4 kW	Weight:	2294 kg
Voltage / Frequency:	400 V / 50 Hz	Type of consumables:	Wire
Cycle time when idling:	25 s	Press material:	Cardboard, Punch waste/residue, Mixed paper, Plastic film
Volume throughput in idle operation (theor.):	13,75 m ³ /h		
Loading height:	1115 mm		

Product information



To fill the press, the upper half of the doors is swung to the right



Hand wheel door lock - Easy to handle thanks to counter-rotating thread for quick opening and closing



The HSM V-Presses are highly energy efficient thanks to the rapid stroke technology. This saves time and money





Compresses cardboard and film

Suitable for cardboard as well as film.



Automatic start

Automatic start of the pressing process after closing the door.



Economical

Optimised bale dimensions and bale weights for efficient storage, transport and direct commercialisation.




Graphic-capable display

Convenient membrane keypad with text display, which shows the current status of the machine.



HSM TCS

HSM TCS (Torsion Control System) for monitoring press ram movement.



Strapping

Strapping with wire - optional tape station available for strapping with polyester tape or wire according to requirements.



www.tuev-sued.de/ps-zert