



HSM VK 3008

Channel baling press HSM VK 3008

For industrial applications with small material loads - Troughput up to approx. 197 m³/h

Technical data

Order number:	6644001	Loading aperture width x Loading aperture length:	620 x 800 mm
Pressing power:	310 kN	Bale width x Bale height x Bale length:	700 x 800 x 600-1200 mm
Specific pressing power:	55,4 N/cm ²	Length x Width x Height:	6498 x 2951 x 2030 mm
Driving power:	22 kW	Weight:	6,3 t
Voltage / Frequency:	400 V / 50 Hz	Type of consumables:	Wire
Cycle time when idling:	8,2 s	Press material:	Plastic film, Mixed paper, Cardboard
Volume throughput in idle operation (theor.):	197 m ³ /h		
Volume throughput at 50kg/m³ (theor.):	9.85 t/h		

Product information



Particularly suitable for compression of paper, cardboard and plastic film



Versatile solution for materials up to approx. 50 kg /m³ bulk weight



Fast cycle times, 800 mm loading aperture



System solution

Integration into automated industrial production processes.



Continuous loading

Suitable for continuous loading with conveyor belt, air feeding or similar.



Optimized pressing

High bale density and high bale weights.



Automatic operation

Control of the pressing process via light barrier.



Operating side

Can be fully integrated into existing workflows and processes. Operating side can be selected.



Variety of uses

Suitable for almost all requirements. Contact us if you have other materials or applications. We will find you a suitable solution.

